



Georgia Analyzer System Message

Georgia's Clean Air Force (GCAF)

January 13, 2010

Message: 43416 Analyzers: 1019

Analyzer Weather Station

PRINT THIS MESSAGE, PROVIDE TO STATION OWNER OR MANAGER AND POST A COPY NEAR THE PHONE FOR REFERENCE.

Weather stations must remain within the recommended temperature and humidity range for your analyzer in order to conduct an accurate ASM or TSI test.

Analyzers should not be used for ASM or TSI tests if the ambient temperature is above or below the temperature range recommended by the state. The temperature range is 41-110 degrees Fahrenheit.

If your analyzer is outdoors during cold weather, we suggest using an enclosure to maintain the machine at optimal operating conditions.

During cold weather, agitate the calibration gas bottle prior to conducting a three-day calibration. Not agitating the bottle may result in your analyzer failing the calibration and ultimately causing the calibration gas bottle to be unusable due to improper gas mixture.

Ensure that your analyzer is not directly exposed to heating units in your garage.

For assistance regarding the functionality of your weather station, especially during times of extreme cold or heat, contact your EM or review the Inspector Training Manual.

If you would like to receive an e-mail copy of GAS messages or to be added to our quarterly e-newsletter, *RepairWatch E-News*, please send a request to info@cleanairforce.com.

~ GCAF and EPD require that you print, read, and store all GAS messages in a binder on or near the analyzer. GCAF and EPD also recommend that you print a second copy of these messages and post them in a prominent location for your employees to read. To retrieve and print a previous GAS message, go to the GAS message retrieval function in your analyzer and select the appropriate message to print (the analyzer holds up to 500 messages). ~

800.449.2471

info@cleanairforce.com

CleanAirForce.com